



A	Table Size	36"
B	Length- Center- Back	32"
C	Overall Width	30"
D	Base Length	44"
E	Tilt Axis Height	40"



Model P30F CWI- 3000 Positioner

P30F has a motorized variable speed rotation with Forward-Stop-Reverse. The rotation speed is variable from 0.05 to 2.0 RPM with 115 degree forward tilt powered by a 3/4 H.P. DC brakemotor. A self locking gear reducer and spur gear produces a torque of 36,000- inch pounds. A 36" round table with 3 pre-drilled holes is standard for easy chuck mounting. The positioner operates on 115 volt, single phase, 60 cycle input power. Hand pendant includes a "Forward-Stop-Reverse" switch along with a speed adjustment potentiometer on 25' of cable. Standard pre-loaded Sealed bearings are protected by a heavy-duty welding rotoground assembly.

- Load Capacity3000 Lb. 6" overhung from face of table.**
- Rotational Motor Size.....3/4 H.P. DC Motor**
- Rotation Speed.....05 to 2.0 RPM**
- Rotation Torque.....18,000 Inch Lbs.**
- Tilt Range.....0 through 115 degrees, power tilt w/ limit switches**
- Tilt Torque.....45,000 Inch Lbs.**
- Shipping Weight.....1260 Lbs.**
- Swing Radius.....38-3/4" @ 90 degrees**
- Built In Rotary Ground**
- Optional Variable Speed Foot Control**

